




Select the unit online in a few clicks and get full technical data at blaubergselector.com

READING THE MODEL CODE



BLAUAIR RP

Ceiling mounted heat recovery units

Blauberg Ventilatoren
174 N. 36th Street
Lafayette, IN 47905
tel.: +1 765 780 7139


info@blauberg.us
www.blauberg.us
www.blaubergventilatoren.de

Technical changes reserved.
Illustrations and texts are non-binding.

BLAUAIR RP

Premium range of ceiling mounted heat recovery units for commercial applications.

The unit is available in three sizes with rated air flow 500–1500 CFM, with heaters and cooling coils.



FANS

Fans with EC motors. Impellers with backward-curved blades.

Low power consumption at any speed, low noise and stable operation in any climate.

CONTROLS

Integrated plug-and-play controls based on **Carel kVent controller**.



Easy connectivity via Web interface by Ethernet cable. **Modbus** and **Bacnet** protocols.



USER PANELS

S30 th-Tune: simple control panel ensures basic setting options with user-friendly interface.



S32 pGDe: extended control panel for full functionality engineering adjustment.



FRAMELESS CASING SYSTEM

Casing panels made of zinc -aluminum coated steel with a 1 9/16" mineral wool heat- and sound-insulating layer. Corrosion class C4 according to ISO 12944: class C4. Each model available in left or right versions. Service access from the bottom.

HEAT RECOVERY CORE

High-efficient rotary heat recovery core is available in two types:

- Condensing (aluminum) type - standard;
- Enthalpy type for hot and humid areas - optional.

DAMPERS

Integrated automatic external dampers with **Belimo** drives. Included in units starting from 1500.



FILTERS

Panel MERV 13 class filters on both supply and exhaust.